

Reestablish a obliterated 1/4S Bet Sec 22 &
23 Town 19 North Range 15 East Town of Winnebago

8

1/4S Road		1/4S Road	
F Eckstein 40A	M.J. Cory	G. Beiser 40A	G. Beiser 40A
F Lightfoot 40A	F. Lightfoot 40A	G. Beiser 40A	G. Beiser 40A
F Lightfoot 40A	F. Lightfoot 40A	Unknown 40A	Unknown 40A
F Lightfoot 40A	F. Lightfoot 40A	C. Nicols	Unknown 30A

To indicate a monument of some kind and could find nothing so I placed this 1/4S where the weight of all the evidence I could get by measurement carefully done and testimony of good respectable settlers I set for 1/4S bet Sec 22 & 23 a 2 inch gas pipe marked with cold chisel 1/8 Sec 22 on west side 1/4S 23 on E side drove it 4 ft in the ground left 1 1/2 ft out of ground with figures in plain sight I gave a copy of these notes to Fred Lightfoot. Began April 20th 1905 Completed April 21st 1905 W W Gould Surveyor W W Gould Chairman Fred Lightfoot

At N E corner of Sec 22 I found stones set for corner by Co Surveyor I ran south bet Sec 22 & 23 V 4 at 40.00 I could find nothing to indicate a corner I used every means available to locate it took a small iron rod and probed the ground all around where it should be to ascertain if there should be a stake or part of stake stone or anything to locate it but could find nothing so I went to the 1/8S 20.00 East from N E corner of Sec 22 at this 1/8 stake I found two R.Ts that had been established by Co Surveyor the Bearings were two Burr Oaks agreeing by distance and course with Co Surveyors measurement at the time this stake was established I found a wire fence running south from this 1/8 stake that was staked out by Co Surveyor verified by C H Gane & F Lightfoot I found that the fence ran south at a V of 3°56' so I ran south at this variation at 19.90 a fence running E & W that was located by Co Surveyor as a line fence bet the NE NW & SE NW of Sec 23 and it agreed with Co field notes verified by C H Gane & F Lightfoot so I took this fence as the Right line bet the two described 40s and continued my line south at 39.80 I set a gas pipe for corner 2 inches in diameter marked with cold chisel 1/8S I then ran west on a parallel line with the Road on N side of Sec at V 2°45' along this line at every 5.00 I set a wooden stake for a guide to build a line fence bet F Lightfoot & F Eckstein land at 20.00 I closed in at an old line fence that had stood there for years built according to Co Surveyors measurement and my measurement agreeing with Co Surveyors measurement and taking the evidence of F Lightfoot a man that had lived there since he was born that it was about the spot that the 1/4S should be after I had used every thing within my power to locate something to

CITY OF OSHKOSH
ENGINEERING DEPARTMENT

DRAWN
SCALE

ReESTABLISH A OBLITTERATED 1/4S Bet Sec 22
& 23 TOWN 19 NORTH RANGE 15 EAST TOWN OF
WINNECONNE WINNEBAGO CO WIS.